



**FUKUCOM COMPANY LTD.**

**福 靈 有 限 公 司**

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,  
KWUN TONG, KOWLOON, HONG KONG.

TEL: 852-2790 0314 FAX: 852-2790 0206


## ST 78L09

---

### 3-Terminal positive voltage regulator

9V

- Suitable for TTL, DTL, HTL, C-MOS, Power Supply
- Internal Short-Circuit Current Limiting
- Internal Thermal Overload Protection
- Maximum Output Current of 150mA ( $T_j=25^{\circ}\text{C}$ )
- Available in the Plastic TO-92 Package




1. Output 2. Common 3. Input

TO-92 Plastic Package  
Weight approx. 0.19g

### Absolute Maximum Ratings ( $T_a = 25^{\circ}\text{C}$ )

	Symbol	Rating	Unit
Input Voltage	$V_{IN}$	35	V
Power Dissipation	$P_{tot}$	800	mW
Operating Temperature	$T_{opr}$	-30~75	$^{\circ}\text{C}$
Storage Temperature Range	$T_s$	-55~150	$^{\circ}\text{C}$



**SEMTECH**

Dated : 07/12/2002



**FUKUCOM COMPANY LTD.**

**福 靈 有 限 公 司**

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,  
KWUN TONG, KOWLOON, HONG KONG.


TEL: 852-2790 0314 FAX: 852-2790 0206

## ST 78L09

### Electrical Characteristics

(Unless otherwise specified,  $V_{IN}=15V$ ,  $I_{OUT}=40mA$ ,  $C_{IN}=0.33\mu F$ ,  $C_{OUT}=0.1\mu F$ ,  $T_J=25^\circ C$ )

	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Output Voltage	$V_{OUT}$		8.64	9	9.36	V
Input Regulation	Reg. line	$11.4V \leq V_{IN} \leq 24V$	-	80	200	mV
		$12V \leq V_{IN} \leq 24V$	-	20	160	
Load Regulation	Reg. load	$1.0mA \leq I_{OUT} \leq 100mA$	-	17	90	mV
		$1.0mA \leq I_{OUT} \leq 40mA$	-	8	45	
Output Voltage	$V_{OUT}$	$11.4V \leq V_{IN} \leq 24V$ $1.0mA \leq I_{OUT} \leq 40mA$	8.55	-	9.45	V
	$V_{OUT}$	$V_{IN}=15V$ $1.0mA \leq I_{OUT} \leq 70mA$	8.55	-	9.45	V
Quiescent Current	$I_B$		-	3.2	6.5	mA
Quiescent Current Change	With line	$\Delta I_B$	-	-	1.5	mA
	With load	$1.0mA \leq I_{OUT} \leq 40mA$			0.1	
Output Noise Voltage	$V_{NO}$	$T_a=25^\circ C$ , $10Hz \leq f \leq 100KHz$	-	65	-	$\mu V$
Ripple Rejection	RR	$f=120Hz$ , $12V \leq V_{IN} \leq 24V$ , $T_J=25^\circ C$	36	44	-	dB
Dropout Voltage	$ V_{IN}-V_{OUT} $	$T_J=25^\circ C$	-	1.7	-	V
Average Temperature Coefficient of Output Voltage	$TC_{VO}$	$I_{OUT}=5mA$	-	-0.85	-	$mV/^\circ C$



**SEMTECH**

Dated : 07/12/2002