



# FUKUCOM COMPANY LTD.

## 福 靈 有 限 公 司

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,  
KWUN TONG, KOWLOON, HONG KONG.

TEL: 852-2790 0314 FAX: 852-2790 0206

### MPSA44

#### NPN Silicon Epitaxial Planar Transistor

for high voltage switching and amplifier applications.

As complementary type the PNP transistor MPSA94 is recommended.

On special request, these transistors can be manufactured in different pin configurations.




1. Emitter 2. Base 3. Collector  
TO-92 Plastic Package

#### Absolute Maximum Ratings ( $T_a = 25\text{ }^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	$V_{CBO}$	500	V
Collector Emitter Voltage	$V_{CEO}$	400	V
Emitter Base Voltage	$V_{EBO}$	6	V
Collector Current	$I_C$	300	mA
Power Dissipation	$P_{tot}$	625	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 55 to + 150	$^\circ\text{C}$

#### Characteristics at $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit
DC Current Gain				
at $V_{CE} = 10\text{ V}$ , $I_C = 1\text{ mA}$	$h_{FE}$	40	-	-
at $V_{CE} = 10\text{ V}$ , $I_C = 10\text{ mA}$	$h_{FE}$	50	200	-
at $V_{CE} = 10\text{ V}$ , $I_C = 50\text{ mA}$	$h_{FE}$	45	-	-
at $V_{CE} = 10\text{ V}$ , $I_C = 100\text{ mA}$	$h_{FE}$	40	-	-
Collector Base Cutoff Current at $V_{CB} = 400\text{ V}$	$I_{CBO}$	-	0.1	$\mu\text{A}$
Collector Emitter Cutoff Current at $V_{CE} = 400\text{ V}$	$I_{CEO}$	-	0.5	$\mu\text{A}$
Emitter Base Cutoff Current at $V_{EB} = 4\text{ V}$	$I_{EBO}$	-	0.1	$\mu\text{A}$
Collector Base Breakdown Voltage at $I_C = 100\text{ }\mu\text{A}$	$V_{(BR)CBO}$	500	-	V
Collector Emitter Breakdown Voltage at $I_C = 1\text{ mA}$	$V_{(BR)CEO}$	400	-	V
Emitter Base Breakdown Voltage at $I_E = 100\text{ }\mu\text{A}$	$V_{(BR)EBO}$	6	-	V
Collector Emitter Saturation Voltage				
at $I_C = 1\text{ mA}$ , $I_B = 0.1\text{ mA}$	$V_{CE(sat)}$	-	0.4	V
at $I_C = 10\text{ mA}$ , $I_B = 1\text{ mA}$	$V_{CE(sat)}$	-	0.5	V
at $I_C = 50\text{ mA}$ , $I_B = 5\text{ mA}$	$V_{CE(sat)}$	-	0.75	V
Base Emitter Saturation Voltage at $I_C = 10\text{ mA}$ , $I_B = 1\text{ mA}$	$V_{BE(sat)}$	-	0.75	V
Collector Output Capacitance at $V_{CB} = 20\text{ V}$ , $f = 1\text{ MHz}$	$C_{ob}$	-	7	pF





# FUKUCOM COMPANY LTD.

福靈有限公司

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,  
KWUN TONG, KOWLOON, HONG KONG.

TEL: 852-2790 0314 FAX: 852-2790 0206

## MPSA44

